



## RUBINETTO ALTO ELETTRONICO AD AZIONAMENTO A SENSORE CON REGOLAZIONE ACQUA CALDO/FREDDO TRAMITE DUE RUBINETTI SOTTOLAVABO CON FILTRO

Electronic high tap with sensor control, for pre-mixed water equipped with two angle valves with filter

D0SE17L/99      **cm**  
30,3



Cromo

99

testo di capitolato:

rubinetto alto elettronico cromato ad azionamento a sensore con regolazione acqua caldo/freddo tramite due rubinetti sottolavabo con filtro. con aeratore M24. alimentazione con 4 batterie da 1,5V tipo AA al litio incluse. pressione di lavoro 1-6 bar. temperatura acqua max 80°C. ingressi G1/2" M. raggio d'azione predisposto 10 cm. portabatterie IPX5. connessioni IPX5. Elettronica omologata CE.

dimensioni mm. 303x170x50.

Goman Tipo codice D0SE17L/99

specifications:

High chromed electronic sensor operated faucet with hot/cold water adjustment by means of two angle valves with filter. with M24 aerator. power supply with 4 1.5V type AA lithium batteries included. working pressure 1-6 bar. water temperature max 80°C. G1/2" M inputs. range of action arranged 10 cm. IPX5 battery holder. IPX5 connections. CE approved electronics.

Goman Type code D0SE17L/99

